

CELLPHONE MONITOR **WATCHHOUND**



24 - 7 CELL PHONE SECURITY MONITOR NETWORK

WatchHound™ continuously scans cellphone prohibited areas for wireless activity, essentially creating wireless-free zones. Just mount it to any wall and turn it on to begin monitoring.

**PLUG & PLAY SIMPLE
NO ADJUSTMENTS NEEDED**

**YOUR 24-7
CELLPHONE
MONITOR**

WatchHound's built in speaker, ultra-bright OLED, Power over Ethernet, simple thumbball operation and dry contacts for external alerts allow for an all-in-one cell phone security monitor without need for additional security personnel.

WatchHound™ supports Direction Finding Antennas for narrow, sensitive hallway or corridor scans. All threshold settings are user adjustable directly on unit or via optional PC monitoring software. Covert models disguised as common thermostats are also available to secretly monitor any environment.

**CUSTOM
USER
SETTINGS**



Prisons & Correctional Facilities • Government & Military Installations • Law Enforcement Agencies • Financial Institutions • Universities • Court Rooms

+1 732-548-3737
www.bvsystems.com
sales@bvsystems.com



CELLPHONE MONITOR **WATCHHOUND**



24 - 7 CELL PHONE SECURITY MONITOR NETWORK

SPECIFICATIONS:

U.S. BANDS

LTE Uplink 699-716 MHz
LTE Uplink 777-787 MHz
LTE Uplink 788-798 MHz
824-849 MHz
896-901 MHz
AWS Uplink 1710-1755 MHz
1850-1910 MHz
2305-2315 MHz

INTERNATIONAL BANDS

EU
Australia
New Zealand
Israel
Sweden
Brazil
Japan
Canada

EUDD 832-862 MHz MHz
EGSM 880-915 MHz
DCS 1710-1785 MHz
IMT 1920-1980 MHz
IMT-E 2500-2570 MHz

Check with our sales team to include your country's band

RADIUS OF COVERAGE AREA 150 feet (~50 meters) under typical conditions

DYNAMIC RANGE 60 dB

SENSITIVITY -83 dBm

DETECTOR RESOLUTION 2 dB

BANDWIDTH RESOLUTION 4 MHz / 20 MHz

SELECTIVITY REJECTION >50 dB @ 1 MHz from uplink band edges

ANTENNAS SUPPORTED Optional Direction finding (field-swappable multiband panel antenna with SMA connector)
Included Omni-directional (quarter-wave multiband, monopolar antenna with SMA connector)
Integral/Covert (optional quarter-wave, multi-band, monopole connected internally, 10 dBi gain)
SMA jack for external antenna

RF INPUT

MINI-USB PORT

DC POWER INPUT

Mini-USB jack for monitoring & logging cellular usage via a PC network

DC jack for connecting to a supplied external AC power supply
(Optional external battery hidden behind unit)

LAN INTERFACE

Power Over Ethernet capable

DRY CONTACT PORT

Polarity insensitive, for triggering other devices

AUDIO ALERT

Audio alert message via loudspeaker

VISUAL ALERTS

LCD screen, mini-trackball illumination (red or blue)

TACTILE INPUTS

Compact, pushbutton trackball for versatile control

WEIGHT

Under 1lb. with omni-directional antenna (less than 2lb. (30 oz.) with directional antenna)

INTEGRAL ATTENUATOR

0 to 30 dB, user-selectable via soft menu

SENSITIVITY RANGE

-80 to -50 dBm, user-selectable via soft menu

DATA LOGGING


Optional PC software



WatchHound ships with ethernet and power cables, AC power adapter, omni-directional antenna and SD card including user manual



*Also ask about our covert
thermostat WatchHound!*



WatchHound optional PC security software displays realtime network alerts and parameters from any WatchHound unit on the network.

Prisons & Correctional Facilities • Government & Military Installations • Law Enforcement Agencies • Financial Institutions • Universities • Airports

+1 732-548-3737

www.bvsystems.com

sales@bvsystems.com

