

RF security experts, thousands of cell detectors to law enforcement and corrections agents around the world."



Scott Schober - Berkeley CEO, Wireless Tech & Cybersecurity Expert

Pocket-sized, covert contraband cell phone detection



+1 732-548-3737 www.bvsystems.com sales@bvsystems.com





## **COUNTRIES SUPPORTED:**

United States
Canada
EU
Australia
New Zealand
Israel
Sweden
Brazil
Japan
China
Chile

India



Check with our sales team for your country's band selection including possible custom set of bands

FREQUENCY RANGE	600-3800 MHz (includes all cellular devices as well as GPS trackers)		
DETECTION RANGE	Environment	Interference	Approximate Distance
	Indoors	None (line of sight)	150 feet
1900 - Lan	Indoors	Walls, windows, doors, etc.	75 feet
	Indoors	Rebar concrete or steel	40 feet
the state of the s	Outdoor use	None (line of sight)	1/2 mile
	Outdoor use	Buildings, trees, etc.	125 feet
DYNAMIC RANGE	70 dB		
SENSITIVITY	-90 dBm		
BANDWIDTH RESOLUTION	4 MHz, 20 MHz		Days.
SELECTIVITY REJECTION	Better than 40 dB		
RECEIVING MODES	High-speed active scanning		
ANTENNAS SUPPORTED	Removable omni-directional SMA connection		
POWER REQUIREMENTS	Internal built-in 3.2 Ah Li-Ion battery / external 12 VDC nominal		
CHARGING	4-5 hours (may be charged while in operation but not recommended for daily use)		
BATTERY RUNTIME	Up to 4 hours		
DISPLAY & CONTROL	240 x 320 sunlight readable color TFT with a resistive touch screen		
UNIT DIMENSIONS	5.5" x 3" x 1.25"		
DOCK DIMENSIONS	4" x 3" x 2"		
DOCK COOLING	Dual fans with manual switch for prolonged operation during charging		
PORTS	Mini-USB		
ALERTS	Vibration (toggleable) and visible (blue LED on top of unit)		
SOUND	Audible feedback from touchscreen taps		
INCLUDED ACCESSORIES	Omni-directional SMA antenna, 12 VDC power adapter, charging dock, carrying case		

